



Two PTO speeds available (540/540 ECO)



Original cab with tiltable and adjustable steering column

4E SERIES

4090.4E

THE PERFECT CONFIGURATION.

4090.4E

Unrivaled power and versatility.

If versatility is a priority and you're looking for a tractor with a low weight to power ratio that meets your exact needs for productivity, the new 4090.4E Series is the perfect answer for you, whatever the task.

●: standard ○: optional -: not available

The technical data and pictures are guideline only. Committed to delivering a product more and more in line with your needs, DEUTZ-FAHR reserves the right to update the specifications of its machines at any time.

MACHINE SPECIFICATIONS		4090.4E
ENGINE		
Manufacturer		SDF
Model		1000.4WTI
Emissions		Stage III A
Cylinders/Displacement	n°/cc	4/4000
Intake		Turbo Intercooler
Max. power	kW/HP	62.5/85
Maximum torque	Nm	348
Air filter with dust ejector		-
Fuel tank capacity	liters	70
TRANSMISSION		
Number of speeds with splitter		30F+15R
Number of speeds with supercreeper gear		-
Minimum speed with supercreeper gear	km/h	0.23
Maximum speed	km/h	40
PTO		
Rear PTO	rpm	540/540ECO
Ground speed PTO		●
AXLES AND BRAKES		
4WD front axle with brakes		●
Front wheel drive engagement		Mechanical
Front and rear differential lock engagement		Mechanical
Hydrostatic steering with independent pump		●
HYDRAULIC SYSTEM AND Lift		
Opencentre hydraulic system pump flow (standard)	l/min	42
Auxiliary rear mechanical distributors	n°	3
Rear lift control (Mechanical)		●
Rear lift capacity	kg	3500
DRIVING POSITION		
Platform		○
Side mounted levers		●
Cab/ROPS		○
DIMENSIONS AND WEIGHTS		
Width (min.-max.)	mm	1799-1941
Wheelbase (4WD)	mm	2106
Total unladen weight (min.-max.)	kg	3100-3250